

FLAMESHIELD 300 & FIRE WATER MAINS/DELUGE HOSE



HIGH PRESSURE OILFIELD HOSE

APPLICATION

Seawater Delivery Hose 21 Bar / Deluge System Hose

TEMPERATURE	(-30°C to +100°C) (-22°F to +212°F)	
CONSTRUCTION	Tube	Black Nitrile Rubber
	Reinforcement	Steel Braided Layers & Anti-static Copper Wire, Steel Helix Wire included on 6" ID and above
	Cover	Red CR Rubber, Abrasion, Ozone, Weather, Heat & Oil Resistant
STANDARDS	Additional standards/certifications available upon customer request	
COUPLINGS	Crimped	



ID		OD		WORKING PRESSURE		BURST PRESSURE		MBR		WEIGHT		MAX HOSE LENGTH		REFERENCE CODE
inch	mm	inch	mm	bar	psi	bar	psi	inch	mm	kg/m	lb/ft	m	ft	
1 1/2	38	2.91	74	21	305	104	1500	12	0.3	3.8	2.6	60	196	H4F324
2	51	3.11	79	21	305	104	1500	16	0.4	4.8	3.2	60	196	H4F332
3	76	4.21	107	21	305	104	1500	20	0.5	7.0	4.7	60	196	H4F348
4	102	5.28	134	21	305	104	1500	24	0.6	7.5	5.0	60	196	H4F364
5	127	6.14	156	21	305	104	1500	41	1.0	9.5	6.4	60	196	H4F380
6	152	7.24	184	21	305	104	1500	45	1.1	14.0	9.4	60	196	H4F396
8	203	9.53	242	21	305	104	1500	49	1.3	22.0	14.8	60	196	H4F3128
10	254	11.61	295	21	305	84	1218	63	1.6	25.0	16.8	60	196	H4F3160

Gates Corporation is a leading manufacturer of application-specific fluid power and power transmission solutions. At Gates, we are driven to push the boundaries of materials science to engineer products that continually exceed expectations.