BP20S BULK PRODUCT DELIVERY HOSE 20 BAR



HIGH PRESSURE OILFIELD HOSE

APPLICATION

Heavy duty barite and cement

| TEMPERATURE | (-35°C to +85°C) (-31°F to +185°F) | | | | | | | |
|--------------|---|-------------------------------------|--|--|--|--|--|--|
| CONSTRUCTION | Tube | High Tensile Synthetic Textile | | | | | | |
| | Delafananant | Black IR/BR Blend Rubber | | | | | | |
| | Reinforcement | Abrasion, Ozone & Weather Resistant | | | | | | |
| | Cover | Heavy duty barite and cement | | | | | | |
| STANDARDS | Additional standards/certifications available upon customer request | | | | | | | |
| COUPLINGS | Crimped | | | | | | | |













| ID | | OD | | WORKING PRESSURE | | BURST PRESSURE | | MBR | | WEIGHT | | MAX HOSE LENGTH | | REFERENCE CODE | REFERENCE NUMBER |
|------|-----|------|-----|---------------------|-----|-------------------|------|------|-----|--------|-------|--------------------|-----|-------------------|---------------------|
| inch | mm | inch | mm | bar | psi | bar | psi | inch | mm | kg/m | lb/ft | m | ft | | |
| 4 | 102 | 5.00 | 127 | 20 | 300 | 80 | 1200 | 40 | 1.0 | 5.0 | 3.4 | 60 | 196 | H2BP20S64 | - |
| 5 | 127 | 5.98 | 152 | 20 | 300 | 80 | 1200 | 50 | 1.3 | 6.6 | 4.4 | 60 | 196 | H2BP20S80 | - |

Gates Corporation is a leading manufacturer of application-specific fluid power and power transmission solutions. At Gates, we are driven to push the boundaries of materials science to engineer products that continually exceed expectations.